

# IMPACDOR®

## RD-175



**The Aleco ImpacDor® RD-175** is a durable, lightweight, attractive door with stainless steel hardware, insulated panel and full perimeter seal ideal for rack, push cart and pallet jack traffic.

The Aleco ImpacDor® RD-175 is designed for effortless swing using the EZ Hinge stainless steel upper hinge and 8-3/4" h stainless steel lower jamb guard. The Aleco RD-175 is constructed from rigid PVC sub-frames ultrasonically welded to the 1/8" thick ABS facings available in 12 colors. The internal closed cell foam insulation provides an R-value of 13. The Aleco RD-175 is constructed without wood, glue or rivets and is ideal for wash down applications when ordered with the single pane window option.



### Superior perimeter seal design for a superior seal

The Aleco RD-175 features a fully replaceable perimeter seal including the leading edge of each panel. Leading edge seals are extruded from USDA and FDA accepted Neoprene material. Ideal for any application where a durable, tight sealing, insulated, energy saving door is desired.

### Dual pane windows

The Aleco RD-175 windows feature sealed dual pane construction for superior insulation qualities. Windowpanes are 1/8" clear polycarbonate mounted in ABS frames for long-term durability.

### The perfect retail door

The Aleco RD-175 is ideal for food service, food processing, retail, supermarket and light industrial applications. The total panel thickness is 1-3/4" and is custom constructed to your requirements +/- 1/8" of actual net opening width and height. The RD-175 provides smooth, quiet and easy double-action opening up to 125 degrees in either direction so the door swings out of traffic's way without over extending the hinge.

### Available Options:

- Molded polyethylene bumpers from 12" to 48" tall
- Impact panels up to 48" tall
- 3/4" rise V-cam hardware
- Choice of colors:  
Cloud Gray, Charcoal Gray, Black, Cadet Blue, Cocoa, Chocolate, Beige, Red, Burgundy, White, Royal Blue, Green

**Food Processing Plants**

**Food Service**

**Retail Stores**

**Pharmaceutical and Medical Facilities**

**Light Industrial**

### Features:

- Lightweight, insulated full thickness 1-3/4" (44mm) door
- Internal extruded PVC framework uses no wood
- Ultrasonically welded ABS facings-no adhesive, screws or rivets
- Closed cell foam insulation
- EZ hinge hardware provides 125 degree swing in both directions
- Stainless Steel EZ hinge with stainless steel jamb guards
- Easy installation
- Low maintenance
- Dual pane thermal windows with single pane available for wash down applications

**ALECO®**  
E.S. ROBBINS

2720 East Avalon Avenue  
Muscle Shoals, AL 35661

Toll Free Phone: 1-800-633-3120  
Toll Free Fax 1-800-750-9616