



2720 E. Avalon Ave.
Muscle Shoals, AL 35661
1-800-633-3120
www.aleco.com

SECTION 08 38 13
FLEXIBLE STRIP DOOR
[Clear-Flex® II Strip Door System]

GENERAL NOTES TO SPECIFIER:

EDIT CAREFULLY TO SUIT PROJECT REQUIREMENTS. MODIFY AS NECESSARY AND DELETE ITEMS THAT ARE NOT APPLICABLE.
VERIFY THAT REFERENCED SECTION NUMBERS AND TITLES ARE CORRECT.

PART 1 GENERAL

1.1 SUMMARY

- A. Section Includes: Flexible Strip Door

1.2 SUBMITTALS

- A. Reference Section 01 33 00–Submittal Procedures; submit the following items:
 - 1. Product Data.
 - 2. Shop Drawings: Show fabrication details and anchorage.
 - 3. Quality Assurance/Control Submittals:
 - a. Manufacturer’s Installation Instructions.
 - b. Manufacturer’s storage and handling instructions.
 - 4. Closeout Submittals:
 - a. Cleaning and Maintenance instructions.

1.3 QUALITY ASSURANCE

- A. Qualifications:
 - 1. Manufacturer Qualifications: Regular manufacturer of flexible strip doors for at least five years.

1.4 DELIVERY STORAGE AND HANDLING

- A. Reference Section 01 66 00–Product Storage and Handling Requirements.
- B. Store per manufacturer’s recommendations until ready for use.

PART 2 PRODUCTS

2.1 MANUFACTURERS

- A. Manufacturer: Aleco Division E.S. Robbins Corp.; 2720 E. Avalon Ave.; Muscle Shoals, AL. Telephone: (800) 633-3120, (256) 248-2402. Fax: (800) 750-9616. Website: www.aleco.com

B. Model: Clear-Flex® II Strip Door System

2.2 COMPONENTS

A. Strips:

SELECT STRIPS FROM BELOW OR CONTACT ALECO FOR DETAILS FOR PROJECT APPLICATION.

1. Formulation: Standard PVC
2. Color: Clear
3. Type: [Smooth] [Scratch-Guard®] [Offset-ribbed]
4. Size/Overlap: [4" x .060 (smooth only) / [50%] [100%]
[6" x .060 (smooth only) / [66%] [100%]
[8" x .080] / [50%] [100%]
[12" x .120] / [33%] [66%] [100%]
[16" x .160] / [25%] [50%] [75%] [100%]

OR

1. Formulation: Low-Temp PVC
2. Color: Clear
3. Type: [Smooth] [Scratch-Guard®] [Offset-ribbed]
4. Size/Overlap: [4" x .060 (smooth only) / [50%] [100%]
[6" x .060 (smooth only) / [66%] [100%]
[8" x .080] / [50%] [100%]
[12" x .120] / [33%] [66%] [100%]
[16" x .160] / [25%] [50%] [75%] [100%]

OR

1. Formulation: Low-Temp Reinforced PVC
2. Color: Clear with nylon string reinforcement
3. Size/Overlap: [6" x .060 / [66%] [100%]
[8" x .080] / [50%] [100%]
[12" x .120] / [33%] [66%] [100%]

OR

1. Formulation: Standard PVC
2. Type: Smooth
3. Color: Dark Amber
4. Size/Overlap: [8" x .080] / [50%] [100%]
[12" x .120] / [33%] [66%] [100%]

OR

1. Formulation: Standard PVC
2. Type: Smooth
3. Color: Black, Opaque
4. Size/Overlap: [8" x .080 / [50%] [100%]
[12" x .120] / [33%] [66%] [100%]

OR

1. Formulation: Anti-Static PVC
2. Type: Smooth
3. Color: Clear
4. Size/Overlap: [8" x .080/ [50%] [100%]
[12" x .120] / [33%] [66%] [100%]

Indicate mounting location (side wall or under lintel) on drawings.

- B. Mounting Hardware: [MaxBullet[®] [aluminum] [stainless steel] [HTP silver] [HTP Fluorescent]]
[Universal Mounting System, [aluminum] [galvanized steel]]

2.3 ACCESSORIES

- A. Offset Bracket Kit.
- B. Horizontal Slide Kit.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Examine opening in which door will be installed.
- B. Coordinate with responsible entity to perform corrective work on unsatisfactory conditions.
- C. Commencement of work by installer is acceptance of opening conditions.

3.2 INSTALLATION

- A. Follow manufacturer's instructions.

3.3 ADJUSTING

- A. Follow manufacturer's instructions as required to:
 1. Align strips to ensure most effective seal; field adjust and modify as required for proper fit.

3.4 CLEANING

- A. Clean surfaces soiled by work as recommended by manufacturer.
- B. Remove surplus materials and debris from the site.

END OF SECTION