

Aleco Order Number: _____

Date: ____ / ____ / ____

ALECO® IMPACDOR® HD-175

Specifications: 1 3/4" Insulated, Cross-Rotationally Molded

Please fill out specifications form and send to Aleco.
Add dimensions to illustration below. Signature is
required before production can begin.



IMPORTANT! SIGNATURE REQUIRED BEFORE PRODUCTION

I have reviewed the specifications and authorize Aleco to begin immediate manufacturing of ImpacDor HD-175.

Approved: _____ Date: _____

Company Name: _____ Phone: _____



SPECIAL OPTIONS / NOTES

APPROXIMATE WEIGHT

4.0 lbs. per sq. ft. X _____ sq. ft. = _____ lbs.

Account Number: _____

Sold To: _____
Address: _____

Purchase Order #: _____

Ship To: _____
Address: _____

Special Markings/Instructions: _____

Quantity: _____ Single/Bi-Parting

Net Opening: _____" Wide _____" High

COLOR SELECTION (Circle One)

- Beige • Black • Charcoal Gray • Chocolate
- Cloud Gray • Red • Royal Blue • White

DOOR FEATURES & OPTIONS

SPRING BUMPERS		IMPACT PANELS
24" Wide	42" Wide	_____ " High
[]	[]	[] 12" High
[]	[]	[] 18" High
[]	[]	[] 24" High
[]	[]	[] 36" High
[]	[]	[] 42" High
[]	[]	[] 48" High

WINDOW SIZES (Dual Pane Only)

14" x 22" for door panels less than 36" wide

18" x 22" for door panels 36" wide and over

[] Window Sealed for Wash Down

LOWER HINGE

8 3/4" High Stainless Steel Jamb Guard
is Standard with Helix Hinge.

SEALS Full Perimeter Air Seal is Standard

[] Jamb & Header Only

HINGE Helical Hinge is Standard

JAMB CONSTRUCTION

Helical hinge requires a minimum double 2x4
wood jamb.

Aleco Part Number: _____